

CW120n 31" Mammography Color Display



Main Features

- ✔ 4200 x 2800
- ✔ 1200 cd/m
- ✔ Embedded IQ Sensor®
- ✔ Ambient Sensor
- ✔ Private Lite / Ambient Lite
- ✔ Self DICOM Calibration & Conformance
- ✔ Human Detector
- ✔ Separated UI Display (3.5", 340 x 800)

Environmental Consideration

Temperature	Operating: 0°C ~ 40°C
	Storage: -20°C ~ 60°C
Humidity	Operating: 8% ~ 80%
Certifications and Standards	ANSI/AAMI ES 60601-1, EN60601-1, IEC60601-1, CE, VCCI, KC, C-Tick, FCC

Display Performance

Screen Size	31"
Viewable Image Size	652.68(H)mm X 435.12(V)mm
Display Resolution	4200(H) x 2800(V) Pixels
Brightness	1200 cd/m ²
Contrast Ratio	1500: 1
Viewing Angle	89° / 89° / 89° / 89° (U/D/R/L)
Input Signal	Display Port 1.4
Control Key	Tact Key
Power Supply	External Power
Backlight System	LED
Power Consumption	Max: 170W Typical: 100W
Built-in Sensors	IQ Sensor, DAC, SBC, Human detector
Dimension	689.0(W) x 647.4(H) x 237.0(D)mm (±2)
Weight	20.0Kg / 44.09lb
Screen Protection	Protective Glass

Specifications and features are subject to change without notice. Images shown are for illustrative purpose only. All products names are trademarks or registered trademarks of WIDE Corp. This document is copyrighted. Neither this document, nor any part of it, may be reproduced or copied without written permission of WIDE Corp. Created in Korea. 2021. 05. Ver1.1©MARKSMARKS.NL10-2021

For More Information Contact

Biomedical Equipment Corp. 10421 NW 28TH
ST STE D102, DORAL, FL 33172 USA | **Ph:** 1-305-463-9447
E: info@4biomed.com | **W:** www.4biomed.com